

Toner
Water
(eco) Solvent
UVgel / UV
Latex

Product Description	A non-woven backed textured, vinyl coated, digital printable wall covering. This texture adds a subtle finish which will make small imperfections almost invisible. For colorful and high resolution wall decorations.
----------------------------	--

Weight	350 g/m²	ISO 536	FR classification	B-s1,d0	EN 13501-1:2018
Thickness	510 µm	ISO 534	VOC	A+	ISO 16000-9
Opacity	>98%				

All values listed are target values

Indoor wall covering	Washable and scrubbable (EN259/EN12956), resistant to
Wall graphic	soap, detergents, alcohol, ammonia
Door coverage	Easy application, Paste-the-wall
Interior Decoration	No need to laminate
Hospitality Venues	EPD (Environmental Product Declaration) available
	Colorfastness 7 / 8 ISO 105 B02
	REACH compliant
	CE-marking acc EN 15102:2019

3"core 1300

Refer for our current offering to www.canon-europe.com/mediaguide

Shelf life: 2 years. Temperature 10-35°C, Relative Humidity 30-75%
 Repack opened rolls when not in use. Always store in dark place in original packaging.
 Allow material to adapt to room conditions for 24 hours before printing.

Best results are obtained between 18-25°C and 35-70% RH.
Optimal print conditions may differ from printer-type.

No Material Safety Data Sheet required. Handle waste and used material as industrial waste.

Cold	Warm	Hot
no	no	no

Cold: pressure sensitive
 Warm: heat activated: 85°C - 95°C
 Hot: heat activated: 105°C -130°C

This non-woven wall covering is designed for indoor use only

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations. Check availability of profiles for your printer on www.canon-europe.com/mediaguide



Processing Guidelines

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing. It is recommended to handle the media with cotton gloves. Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects. Load the media with care in the printers. Incorrect loading can cause skewing or creasing. Use a take-up device to prevent wrinkling. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer/ink combinations. Canon Colour profiles include recommended settings for ink restrictions and printer parameters. Depending on fluctuations in environment, printer, ink, media and applications, printer parameters may have to be adjusted slightly, in order to obtain the best results.

Application guidelines

Always pre-test the surface. The product has been used in many places under numerous possible conditions and has proven its reliability and performance.

The base surface should be carefully prepared:

- Remove all old wallpaper (To remove the remains of old adhesives try using a squirting bottle with water and a few squirts of washing up liquid. This works perfectly on most wallpaper adhesives)
- Remove all remnants
- Smooth out any rough surfaces
- Clean with a damp cloth
- Prior to beginning all surfaces should be dry.

Washability

In general; Digitally printed wallcovering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent and a damp cloth. Dabbing – certainly not rubbing is recommended to lift the soil. It is important to rinse off with clean water (absorbent) cloth washing in a low to high vertical action to prevent moisture at skirting level. Bleach, abrasive cleaners and similar compounds must not be used.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.